

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Back to list

JP 06-293499

1-1/1

Next page

From 1

- 1

Count

Display format

Select the type of output.

Display checked documents



Check All

Uncheck All



** Result [P] ** Format(P801) 2004.03.15 1/ 1

C

Application no/date: 1985-136164[1985/ 6/24]
 Date of request for examination: [1985/ 6/24]
 Accelerated examination ()
 Public disclosure no/date: 1986-293499  [1986/12/24]
 Examined publication no/date (old law): 1991- 37439  [1991/ 6/ 5]
 Registration no/date: 1677148[1992/ 6/26]
 Examined publication date (present law): [1993/ 1/13]
 PCT application no:
 PCT publication no/date: []
 Applicant: HITACHI MICROCOMPUT SYST LTD
 Inventor: WATANABE MASAE
 IPC: D06F 43/00 D06F 43/08
 FI: D06F 43/08 A D06F 43/00 Z
 F-Term: 3B155AA01, BA11, CB27, CB32, CB35, CC08, CD07, DA06, GA06, GA25, GB01, HB02, HB09, MA01, MA02
 Expanded classification: 281
 Fixed keyword:
 Citation:
 [19,1990. 9.13,31] (31,JP,Unexamined Patent Publication,1986085994)
 Title of invention: HOUSEHOLD DRY CLEANING APPARATUS BY VOLATILE LIQUID

Abstract: By a thing having the attachment which a washing machine tub is engaged in revolution washing machine tub inner surface of washer, and can be put on, it is cut in dry-cleaning safely.
 Washing machine tub 1 is reversed, and line part 5a is inserted in orifice department 6a of volatilization liquid reservoir 6, and it is loaded.
 Subsequently,
 When volatilization liquid reservoir 6 is made the top, volatilization aqua flows in authority of tsute washing machine tub 1 in orifice department 6a, 5a, it makes laundry in basket 2 soak.
 Enter in revolution washing machine tub 11 of washer, and it is fixed without backlash with attachment 10.
 Subsequently,
 Electric motor of washer is operated, and revolution washing machine tub 11 is rotated, and deliquoring is ground.
 Attachment 10 is taken off, and volatilization liquid reservoir 6 and washing machine tub 1 are started than revolution washing machine tub 11, volatilization aqua reservoir 6 is done below so that * tsuta volatilization aqua does not enter in basket 2 at the bottom of washing machine tub 1, and volatilization aqua is returned in volatilization aqua reservoir 6, the laundry which washing machine tub 1 is removed from volatilization aqua reservoir 6, and portability, external cover 5, inner cap 4 are taken off to safe locality, and did cleaning / deliquoring from within basket 2 is taken out.

